

AD-A044 538

GENERAL ELECTRIC CO PHILADELPHIA PA RE-ENTRY AND ENV--ETC F/G 7/4
REDEFINITION AND IMPROVEMENT OF METAL VAPOR RELEASE TECHNOLOGY.(U)
AUG 77 P D ZAVITSANOS, F N ALYEA, J A GOLDEN F30602-76-C-0131

UNCLASSIFIED

RADC-TR-77-269

NL

| OF |
40
A044538



END
DATE
FILMED

10-77

DDC

AD A 044538

RADC-TR-77-269
Final Technical Report
August 1977



REDEFINITION AND IMPROVEMENT OF METAL VAPOR RELEASE TECHNOLOGY

General Electric Company/RESO

Approved for public release; distribution unlimited.

This research was sponsored by the Defense Nuclear Agency
under Subtask L25BAXHX632, Work Unit 04, entitled
"Improved Barium Releases".

ROME AIR DEVELOPMENT CENTER
Air Force Systems Command
Griffiss Air Force Base, New York 13441


AD No. _____
DDC FILE COPY

DDC
RECEIVED
SEP 26 1977
B

This report has been reviewed by the RADC Information Office (OI) and is releasable to the National Technical Information Service (NTIS). At NTIS it will be releasable to the general public, including foreign nations.

This report has been reviewed and is approved for publication.

APPROVED:

A handwritten signature in dark ink, appearing to read "Joseph J. Simons", written over a horizontal line.

JOSEPH J. SIMONS
Project Engineer

If your address has changed or if you wish to be removed from the RADC mailing list, or if the addressee is no longer employed by your organization, please notify RADC (DAP) Griffiss AFB NY 13441. This will assist us in maintaining a current mailing list.

Do not return this copy. Retain or destroy.

6 REDEFINITION AND IMPROVEMENT OF METAL VAPOR RELEASE TECHNOLOGY.

10 Dr. Peter D. Zavitsanos
Dr. Fred N. Alyea
Mr. Joseph A. Golden

9 Final Technical report Sep 76 - May 77, 1

Contractor: General Electric Company/RESO
Contract Number: F30602-76-C-0131
Effective Date of Contract: 31 March 1976
Contract Expiration Date: 30 June 1977
Short Title of Work: Redefinition & Improvement
of Metal Vapor Release
Technology

11 Aug 77

12 18 p.

Subtask Number: L25BAXHX632
Period of Work Covered: Sep 76 - Jun 77

Principal Investigator: Dr. Peter D. Zavitsanos
Phone: 215 962-3496
Project Engineer: Joseph J. Simons
Phone: 315 330-3575

Approved for public release;
distribution unlimited.

18 RADC

19 TR-77-269

This research was sponsored by the Defense Nuclear Agency
and was monitored by Joseph J. Simons RADC (OCSA).
Griffiss AFB NY 13441 under Contract F30602-76-C-0131

15

DDC
RECEIVED
SEP 26 1977
RECEIVED
B

404 884

mt

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER RADC-TR-77-269	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) REDEFINITION AND IMPROVEMENT OF METAL VAPOR RELEASE TECHNOLOGY		5. TYPE OF REPORT & PERIOD COVERED Final Technical Report Sep 76 - May 77
		6. PERFORMING ORG. REPORT NUMBER N/A
7. AUTHOR(s) Dr. Peter D. Zavitsanos Dr. Fred N. Alyea Mr. Joseph A. Golden		8. CONTRACT OR GRANT NUMBER(s) F30602-76-C-0131
9. PERFORMING ORGANIZATION NAME AND ADDRESS General Electric Company /RESO 3198 Chestnut Street Philadelphia PA 19101		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS R2160201
11. CONTROLLING OFFICE NAME AND ADDRESS Defense Nuclear Agency Washington DC 20305		12. REPORT DATE August 1977
		13. NUMBER OF PAGES 12
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Rome Air Development Center (OCSA) Griffiss AFB NY 13441		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) Same		
18. SUPPLEMENTARY NOTES This research was supported by the Defense Nuclear Agency under Subtask L25BAXHX632, Work Unit 04, entitled "Improved Barium Releases", Monitored by: RADC (OCSA), Joseph J. Simons, Griffiss AFB NY 13441.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Metal Vapor Releases Barium Titanium/Boron Systems European		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report presents the results of laboratory investigations which involved optimization studies of advanced concepts in atmospheric release technology in terms of barium vapor yield (efficiency) and increased safety. One of the most promising reactions which was identified was the reaction between Titanium and boron (in the condensed phase) to form Titanium diboride, and heat. The heat from this reaction is used to vaporize barium. (Cont'd)		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

Laboratory tests of the Titanium/Boron/Barium system produced a maximum yield of Barium vapor in the amount of 41.2% of the total mixture chemical weight.

This research was sponsored by the Defense Nuclear Agency under subtask L25ABXHX632, subtask title: "IR Phenomenology and Optical Code Data Base", work unit 04, work unit title: "Improved Barium Releases". This effort was monitored by Rome Air Development Center, Joseph J. Simons, OCSA, Griffiss AFB NY 13441.

ACCESSION for	
NTIS	Write Section <input checked="" type="checkbox"/>
DDC	BRI Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	LAFL and/or SPECIAL
A	

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	<u>Page</u>
I. INTRODUCTION	1
II. THERMOCHEMICAL CONSIDERATIONS	1
A. Prediction of Barium Vapor Yield Based on the Ti/B Reaction	1
B. Comparison of the Heat Production with Other Mixtures Used for Ion Cloud Generation	6
C. Laboratory Results and Discussions	7
III. ANALYSIS	11
IV. REFERENCES	12

I. INTRODUCTION

Atmospheric experiments involving the release of metal atoms have been a subject of interest for a number of years. The release of barium vapor and its subsequent photo-ionization has been used to provide partial simulation of nuclear detonations. Barium payloads can be utilized in Transionospheric Satellite Communication programs for the purpose of performing propagation experiments in an environment which simulates certain aspects of nuclear detonation.

The objective of this effort was to (a) pursue analytical studies, computations, and consultation for the Defense Nuclear Agency's (DNA) Ad Hoc Panel for Redefinition of Barium Metal Vapor Release Technology for Advanced Communications System Program, and (b) pursue laboratory investigations which involve optimization studies of advanced concepts in atmospheric release technology in terms of barium vapor yield (efficiency) and increased safety.


II. THERMOCHEMICAL CONSIDERATIONS

A. Prediction of Barium Vapor Yield Based on the Ti/B Reaction

The high exothermicity associated with some condensed phase intermetallic reactions was identified (1, 2) as a convenient and potentially effective means of generating metal vapors for atmospheric releases. The reaction between titanium and boron has been used as heat source for atmospheric releases involving aluminum (2) as well as barium (3).

In order for a given scheme to be of practical interest, the following criteria must be satisfied: 1) Reaction can be easily initiated; 2) once initiated the reaction must be self-sustained at a fast rate; 3) the realized temperatures must be high enough to vaporize the metal of interest; 4) the system must be scalable to large quantities, and 5) the reaction should not be explosive.

As previously stated, one of the most promising reactions which was identified was the reaction between titanium and boron (in the condensed phase) to form titanium diboride according to the following stoichiometry:



Due to favorable thermochemical properties, this is a "gasless" reaction, i.e., the only product in addition to heat is the condensed phase of Ti B_2 ; the calculated adiabatic temperature resulting from the above reaction is 4043°K .

In view of the fact that the boiling point of barium (2100°K) is considerably less than the calculated adiabatic temperature, it is safe to assume that the system can be used as "barium vaporizer" by simply adding barium to the mixture. The vapor pressure of barium in comparison to the other two components of the system (Ti and B) is shown in Figure 1. Since the vapor pressure of barium is five to six, orders of magnitude higher than that of Ti and B respectively, it is expected that extremely small amounts of gaseous titanium and boron would be generated during the barium release. Using the thermochemical properties (Table I) which govern the yield of barium vapor, the Ti/B/Ba system was balanced near the boiling point of barium:




FIGURE 1. VAPORIZATION PROPERTIES

TABLE I


THERMOCHEMICAL PROPERTIES OF METALS AND COMPOUNDS (4-8)

Material	Melting		Enthalpy Change $H_{2100} - H_{298}$ (k cal/mole)	Heat of Formation $\Delta H_f(298)$ (k cal/mole)	Vaporization	
	M. P. °K	ΔH (k cal/mole)			B. P. °K	$\Delta H_{(298)}$ (k cal/mole)
Ba	1000	2.3	14.0	0	2100	43.9
Tl	1940	4.0	18.3	0	3575	112.7
B	2300	5.1	10.1	0	3950	129.2-137.9
Tl B ₂	3193	12 + 3	31.7	-71.6	>4000	

TABLE II
THERMOCHEMICAL COMPARISONS

REACTION	Ba	+	CuO	=	BaO	+ Cu	Σ
mol. weight	137.36		79.57		153.26	63.57	216.93
$\Delta H_{298} (k \text{ cal/mol})$	0		-37.3		-132.3	0	-95.0
2100 CpdT + H_{tr}					23.2	15.0	38.2
298							
NET AVAILABLE HEAT:							- 56.5 kcal/mol - 0.26 kcal/g

REACTION	2B	+	Ti	=	TiB ₂	
mol. weight	2x10.82		47.90		69.59	69.59
$\Delta H (298)$	0		0		-71.6	- 71.6
2100 $\int_{298}^{2100} C_p dT + H_{tr}$					31.7	31.7
298						
NET AVAILABLE HEAT:						- 39.9 kcal/mol - 0.57 kcal/g



This suggests that as much as 0.66 gram-atoms (or 90.6g) of Ba could be vaporized by 1 - mole (69.59 g) of Ti B₂ which corresponds to a theoretical efficiency of 56% based on the total chemical weight.

B. Comparison of the Heat Production with Other Mixtures
Used for Ion Cloud Generation

As a baseline comparison, the Ti/B/Ba system was compared with the most widely utilized reaction between Ba and CuO which forms BaO, Cu and Ba(g). The thermochemical properties of these two systems are shown in Table II.

The net available heat for barium vaporization was estimated for both cases as the difference between the exothermicity of the respective reaction minus the energy required to elevate the products to a temperature equal to the boiling point of barium (2100°K).

$$\Delta H \text{ available} = \Delta H_{(298)} - \int_{298}^{2100} \text{CpdT} + H_{\text{tr}}$$

where H_{tr} represents the heat of transition.

For the comparison, the amount of heat which one gram of the initial mixtures evolves is crucial; as shown in Table II, the Ba/CuO reaction evolves $\frac{56.5}{216.9}$

0.26kcal/g while the Ti/B reaction generates $\frac{39.9}{69.54}$ 0.57 kcal/g.

Therefore, the Ti/B mixture is about 2.2 times more efficient than the Ba/CuO mixture.

C. Laboratory Results and Discussion

The Ti/B/Ba mixtures were prepared in a dry box under flowing nitrogen. The barium was in granules ranging in size from 0.1mm - 2mm and was supplied by Ventron (Beverly, Mass.). The mixtures were subsequently loaded into a graphite crucible and fired either in a vacuum tank or into a quartz tube in flowing nitrogen at one atmosphere.*

The reaction crucible shown in Figure 2 has a volume of about 70 cm³ and an orifice 0.5 cm in diameter. It is made of zirconia lined with grafoil to minimize heat losses by conduction. The reaction was initiated with a hot wire (800°C) and the vaporized barium was partly contained inside a quartz tube. Figure 3 shows the conclusion of one such run where the barium has been converted to BaO by atmospheric oxygen.


The vaporization yield was estimated by removing the residual barium from the reaction mixture by boiling in hot water. Subsequent vaporization of the water made it possible to reclaim the residual barium in the form of BaO.

Several concentrations ranging from 22-47% barium (by weight) were studied and the results are shown in Table III.


As expected from theoretical predictions, almost total removal of the available barium took place. The highest yield of 41.2% is indeed impressive. This preliminary study suggests that much higher yields, than previously possible, can now be achieved by this reaction with the additional advantage of increased safety.

*A special pretreatment of the barium granules reduced drastically the oxidation rate and made it possible to carry out the firings in flowing nitrogen at one atmosphere.

FIGURE 2. REACTION CRUCIBLE



- A = Graphite Lid
- B = Zr O₂ crucible
- C = Grafoil Liner
- D = Base
- E = Quartz Tube 1" Diameter
- F = 6-32 Threaded Rod
- G = Reaction Mixture



Reaction
Crucible

Barium Oxide Deposit

FIGURE 3. PHOTOGRAPH OF REACTION CRUCIBLE AND
OXIDIZED BARIUM DEPOSIT

TABLE III

BARIUM VAPORIZATION EFFICIENCY

<u>Mixture</u>	<u>% Ba</u> <u>(in Mixture by Wt.)</u>	<u>Ba - Recovered</u> <u>from Residue (g)</u>	<u>Ba - Vaporized</u> <u>(in g)</u>	<u>% Ba Vaporized</u> <u>(Based on Total Mixture Chemical Wt.)</u>
Ti/B - 17 g				
Ba - 5 g	22	0.78	4.22	19.2
Ti/B - 17 g				
Ba - 5 g	22	0.18	4.82	21.9
Ti/B - 17 g				
Ba - 6.9 g	28.9	9.62	6.28	26.3
Ti/B - 17 g				
Ba - 8.5 g	33.3	0.96	7.54	29.6
Ti/B - 17 g				
Ba - 15 g	46.9	1.8	13.2	41.2

The safety aspect is based on the fact that the Ti/B reaction requires a sustained high local temperature of 800°C for initiation and is insensitive to shock or electrostatic charges.

III. ANALYSIS

Consultation to the DNA/RAAE Ad Hoc Panel No. 3, "Redefinition of Barium Metal Vapor Release Technology for Advanced Communications Systems", was provided by Dr. F. N. Alyea under support of the present contract. Specifically, this effort required consultation with Dr. E. Bauer of the Institute for Defense Analysis and emphasized preparation of the Panel report entitled, "Barium Releases for Communications Experiments."

The work involved writing Chapter V, "Barium Release Phenomenology", general report organization, and considerable text editing, particularly in the appendices. The report has been submitted to DNA for approval.

IV. REFERENCES

1. Zavitsanos, P. D. and Golden, J. A., "Methods for Releasing Metal Vapors in the Upper Atmosphere," RADC-TR-74-138, Final Report, May 1974, (780555).
2. Zavitsanos, P. D., Alyea, F. N., and Golden, J. A., "Aluminum Vapor Release in the Upper Atmosphere," RADC-TR-76-221, Final Report, July, 1976, (A028820).
3. HPREX Final Report, Ballistic Missile Defense, Adv. Tech. Center (BMDATC), Fall 1975.
4. JANAF - Thermochemical Data, Dow Chemical Company, Midland, Michigan.
5. Honig, R. E. and Kramer, D. A., "Vapor Pressure Data the Solid and Liquid Elements," Reprinted from RCA Review Vol. XXIII, 1969.
6. Zavitsanos, P. D., "The Vapor Pressure of Barium," GE Technical Report 68SD331, November 1968.
7. Stull, D. R. and Sinke, G. C., "Thermodynamic Properties of the Elements," Advances in Chemistry, Series 18, November 1956.
8. Hutgren, R., et. al., "Selected Values of Thermodynamic Properties of Metals and Alloys," Dept. of Mineral Technology, University of California, Berkeley